



VENTILATING DEHUMIDIFIER-GSL SERIES

Thenow GSL Series ventilating dehumidifier, with double cold source, Its dehumidifying based not only the compressor but the original capillary water net work, can remove the humidity quickly and thoroughly. That is to say our GSL series are suitable for the user where already with water system(such as capillary network), it can take the full advantage of the exist water dehumidification function to achieve energy saving. Together with the capillary network, customized constant temperature and humidity and oxygen units are available.



Features



Double cold source, humidity efficiency is more quickly and thoroughly



Full heat exchange system, fresh air in and stale air out



Advance touch sensitive panel with intelligent controller and user friendly operation (Air Quality index display)



Standard 485 interface, WIFI available



Air Purification system:

Fresh Air channel: Pre filter + Medium Filter + HEPA Filter

Exhaust Air Channel: Pre filter and photocatalyst activated carbon at option



Technical Datas

Model	Power Supply	Supply Air (m ³ /h)	Fresh Air (m ³ /h)	Exhaust Air (m ³ /h)	Power(W)	Dehumidification (L/D)	Residual Pressure (Pa)	Max Length of Duct(m)	Application Area(m ²)	Noise dB(A)	Size (LxWxT mm)
CXJT50/400-GSL01	1PH/220V/50Hz	400	0~200	0~150	740	50	70	15	<80	55	1270 x 699 x 283
CXJT70/500-GSL01	1PH/220V/50Hz	500	0~250	0~200	1230	70	80	18	<120	58	1270 x 699 x 283